


**Ulrich Heintz** 

**Brown University** 



## hadron colliders/detectors




### LHC schedule

- 2013-2014 LS1 (prepare LHC for design energy, phase 0 upgrades)
- 2015-2017 physics at 6.5-7 TeV
  - $\int \mathcal{L}dt \sim 50 100/fb @ \mathcal{L} \sim 10^{34} / cm^2/s$
  - pile up:  $\langle n \rangle \sim 40$
- 2018 LS2 (injector/LHC upgrade to ultimate lumi, phase 1 upgrades)
- 2019-2021 physics with ultimate LHC parameters
  - $\int \mathcal{L}dt \sim 300/fb \ \textcircled{0} \ \mathcal{L} \sim 2 \times 10^{34} \ /cm^2/s$
  - pile up:  $\langle n \rangle \sim 50 100$
- 2022 LS3 (focusing magnets and crab cavities, phase 2 upgrades)
- 2023-2035 physics with HL-LHC (3000/fb)
  - $-\int \mathcal{L}dt \sim 3000/fb \ @ \ \mathcal{L} \sim 5 \times 10^{34} \ /cm^2/s$
  - pile up:  $(n) \sim 150 250$


# the challenge

• ATLAS  $Z \rightarrow \mu\mu$  event with 25 vertices



# the challenge

12/2012




## tracking detectors

- 250/fb ~ 1.5×10<sup>15</sup> n<sub>eq</sub>/cm<sup>2</sup> for innermost layer
- increased leakage current
  - need to run detectors cold to limit current
- increased bias voltage
  - less charge sharing decreased resolution
  - breakdown
- current detectors designed for ≈500/fb
  - exchange/addition of innermost pixel layer
- need radiation hard material

## tracking detectors


- CMS: HPK project
  - irradiate > 150 Si wafers with protons and neutrons
  - different materials:
    - Float-zone (FZ), Magnetic Czochralski (MCz), Epitaxial (Epi)
  - different thicknesses and technologies
    - n-bulk, p-bulk with p-spray and p-stop isolation, 2nd metal layer
  - different geometries
  - choose material and technology for phase 2 tracker upgrade by early 2013



# tracking detectors

ATLAS n-in-p detectors

### Signal: Charge collection post-rad (RD50)





### 3D silicon detectors

- advantages
  - short drift distances
  - voltage breakdown less likely
  - deplete at lower bias voltages
  - less impact of radiation damage
  - fast charge collection
  - $\mu$ m dead regions at the edges
- disadvantages

10/12/2012


- more processing/expensive
- 25% of ATLAS pixel B layer





# trigger

- keep output rate fixed at 100k
  - increasing input rate
  - larger event size
  - avoid raising thresholds
- better algorithms
- single muon rates saturate
- calorimeter isolation insufficient to control rates
- move capabilities to lower trigger levels
  - L1 track trigger
  - vertexing for pileup rejection
  - finer grained spatial resolution in calorimeter for matching



# CMS L1 track trigger

phase 2

 need to gather data from 10<sup>8</sup> pixels in 200m<sup>2</sup> of silicon at 40 MHz


 power & bandwidth to send offdetector prohibitive

 one of several proposed designs uses 3D electronics to connect a single readout chip to two closely spaced sensors

locally correlate hits to filter on p<sub>T</sub>


off-detector processing in 15°
sectors using state of the art FPGAs

drives tracker design



# ATLAS FastTracKer (FTK)

- phase 1
- Dedicated hardware processor completes track reconstruction by beginning of level-2 processing.



Pattern recognition in coarse resolution (superstrip→road)

Track fit in full resolution (hits in a road)  $F(x_1, x_2, x_3, ...) \sim a_0 + a_1 \Delta x_1 + a_2 \Delta x_2 + a_3 \Delta x_3 + ... = 0$ 

# ATLAS phase 2 track trigger

### **Trigger Bandwidth Solutions**

two baseline concepts for L1 Track Trigger in ATLAS:

#### "Region of Interest"

- spatial cluster filter
- external trigger information (calo, muon, ...)
- new level L0 trigger required
- all tracks in regions

region {


Double Frontend Buffer → talk D.Wardrope

André Schöning, Heidelberg Pl

5

#### "Self Seeded Track Trigger"


- momentum filter of clusters
- cluster size + local coincidence
- special HW design required
- all high p<sub>+</sub> tracks



WIT2012, Pisa, April 3-5, 2012

sa

4




### calorimeter


- radiation damage after LS2
  - loss of light transmission
  - degradation of photo detectors
  - need detailed detector evolution model
- CMS uses particle flow technique for reconstruction
  - energy from charged particles can be associated with vertex using track
  - not possible for energy from neutrals

### calorimeter





# calorimeter pileup mitigation



- time of calorimeter signal at large  $\eta$  depends on position of the collision
- for a luminous region of 10cm, collisions are distributed over 300ps
- need 10~20ps TOF measurement together with tracker coverage
  - tracking identifies location of interesting collision
  - TOF of charged particles from that collision identifies its time
  - use location and time to select calorimeter clusters from this collision
- current state of the art for large scale systems is ~75ps (ALICE TOF)

10~20ps TOF resolution is ambitious...

10/12/2012

### new materials

- forward region is important e.g. for Higgs bosons produced via VBF
- consider new radiation hard materials for forward region
- calorimeter
  - quartz detectors
  - amorphous silicon
- muon detector
  - GEM detectors
  - micromegas


### electronics

move to new platforms developed by

telecommunications industry

• μTCA platform (CMS)

ATCA platform (ATLAS)



### conclusion

- the challenges are obvious
  - high radiation levels
  - large even sizes and rates
  - high pile up

### goal

- identify the challenges and technology issues most critical to achieving the physics goals at the energy frontier
- my list is surely incomplete
- your input is needed

#### thanks to:

 Frank Hartmann, Ron Lipton, Marcello Manelli, Srini Rajagopalan, Roger Russak, Abe Seiden, Wesley Smith, many others...